

R462 Syringe Pump

RWD



R462 syringe pump are widely used in biomedical, animal science, pharmaceutical industry, and other scientific and industrial production fields.

TECHNICAL SPECIFICATIONS

MODE	Infuse/Withdraw
MINIMUM FLOW RATE	0.0001 $\mu\text{L}/\text{min}$ (with 0.5 μL syringe)
MAXIMUM FLOW RATE	102 mL/min(with 60mL syringe)
LINEAR FORCE	50 lb(23kg)
SYRINGE SIZE (MIN/MAX)	0.5 μL to 60mL
STEP RESOLUTION	0.046 $\mu\text{m}/\text{step}$
OPERATIONAL TEMPERATURE	4°C to 40°C (40°F to 104°F)
STORAGE TEMPERATURE	-10°C to 60°C (14°F to 140°F)
ACCURACY	< \pm 0.35%
REPRODUCIBILITY	< \pm 0.05%
CONNECTIVITY	USB-B, BNC, RS485, TTL
POWER	110/220VAC

SELECT APPLICATIONS

Constant velocity mode (Injection; Withdraw; Injection&Withdraw; Withdraw&Injection)

Gradual-change mode

Pulse mode

Operation mode (Constant; Delay; Signal input; Signal output; Gradient Repeat Stop)

RWD Life Science Inc.

Add: 850 New Burton Road, Suite 201, Dover, DE 19904, Kent, Delaware
Tel: (858)900-5879 E-mail: sales@rwdstco.com

Asia warehouse: Unit B, G/F., Golden Bear Industrial Centre, 66-82 Chai Wan Kok Street, Tsuen Wan, New Territories, Hong Kong

RWD R462 syringe pump- Brochure V1.0-20200414-EN

